

RUUD SALES FACT SHEET

U96V- SERIES 96% A.F.U.E.† Models with Input Rates of 60 to 100 kBTU [17.58 to 29.31 kW]



GENERAL TERMS OF LIMITED WARRANTY*

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Heat Exchanger	.Limited Lifetime
Parts	Ten (10) Years
Conditional Unit Replacement	
(Registration /Required)	Ten (10) Years

[†]A.F.U.E. (Annual Fuel Utilization Efficiency) calculated in accordance with Department of Energy test procedures.

*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

Ruud *Ultra*™ Series Two Stage Variable Speed Multi position Gas Furnaces

Features

- Up to 96% residential gas furnace CSA certified
- 4 way multi-poise design
- Two stages of operation to save energy and maintain optimal comfort level
- Variable speed blower motor technology provides ultimate humidity control, quieter sound levels, and year round energy savings.
- EcoNet[™] enabled HVAC Product
- PlusOne[™] Diagnostics 7-Segment LED all units
- PlusOne[™] Ignition System DSI for reliability and longevity
- PlusOne[™] Water Management System with patented Blocked Drain Sensor
- Heat exchanger is removable for improved serviceability. Primary is constructed of aluminized steel, secondary is constructed of stainless steel for maximum corrosion resistance and thermal fatigue reliability.
- Low profile "34 inch" cabinet ideal for space constrained installations.
- Blower Shelf design serviceable in all furnace orientations
- Pre marked hoses insures proper system drainage
- Vent with 2" or 3" PVC
- Replaceable Collector box
- Hemmed edges on cabinet and doors
- Quarter turn fasteners for tool less access
- Integrated control boards feature dip switches for easy system set up
- Self priming condensate trap
- Solid bottom included
- Compatible with single or two stage thermostats. For optimal performance a two stage thermostat is recommended.

MODEL	INPUT- BTU/HR [kW] ①	HEATING CAPACITY BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
U96VA060	56,000 [16.41]	53,760 [15.75]	1025 [484]	1050 [496]	128 [58]	
U96VA070	70,000 [20.51]	67,200 [19.68]	1015 [479]	1050 [496]	132 [60]	
U96VA085	84,000 [24.62]	80,640 [23.63]	1470 [694]	1750 [826]	147.5 [67]	
U96VA100	98,000 [38.71]	94,080 [37.16]	1710 [807]	1750 [826]	152 [69]	

Note: Above data and specs are for upflow models.

[] Designates Metric Conversions













RUUD SALES FACT SHEET

U96V ACCESSORIES					
Description	Part No.	Price			
Condensate Pump Kit	1PCB151TUL				
External Bottom Filter (Upflow/Horizontal) Rack	RXGF-CB				
External Side Filter Rack	RXGF-CD				
External Downflow Top Filter Rack	RXGF-CC				
Downflow/Horizontal Conversion Kit	RXGY-CK				
Downflow/Horizontal Left Zero Clearance Conversion Kit	RXGY-ZK				
Combustible Floor Base	RXGC-B17				
Combustible Floor Base	RXGC-B21				
Combustible Floor Base	RXGC-B24				
Direct Vent Furnace Side Wall Vent 2" or 3"	RXGY-G02				
LP Conversion Kit	RXGJ-FP34				
Neutralizer Kit	RXGY-A01				
Return Air Plenum	RXGR-C17B				
Return Air Plenum	RXGR-C21B				
Return Air Plenum	RXGR-B24C				
Vent Termination Kit - Concentric Horizontal/Vertical (US & Canadian Installations) 3" Pipe	RXGY-E03A				
Vent Termination Kit - Concentric Horizontal/Vertical (US & Canadian Installations) 2" Pipe	RXGY-E02A				
Vent Termination Kit - Concentric Horizontal/Vertical (US Installation Only) 2" Pipe	RXGY-E02				
Vent Termination Kit - Concentric Horizontal/Vertical (US Installation Only) 3" Pipe	RXGY-E03				
Indoor Coil Casing	RXBC-D17Al				
Indoor Coil Casing	RXBC-D21AI				
Indoor Coil Casing	RXBC-D24AI				
Indoor Coil Casing	RXBC-D21B1				
Combustion Air Drain Kit 2"	RXGY-D05				
Combustion Air Drain Kit 3"	RXGY-D06				
EcoNet Control	UETST600SYS				
EcoNet Control Wall Plate	RCPN-AMC08				
EcoNet Control Face Plate	UETSTFPL				
EcoNet Translator	RETRN620CC2				